



ISO VIEW
FOR REFERENCE ONLY

NOTES:

1. FITTINGS ARE AVAILABLE AS NPT, SAE, BSP & VCR
2. MAXIMUM OPERATING TEMPERATURE: 800°C
3. ALUMINA HEATER RATED FOR:
 - 60V, 150W
 - 90V, 350W
 - 120V, 625W
4. COMPACT, DURABLE & HIGHLY EFFICIENT HEAT EXCHANGE

PROPRIETARY AND CONFIDENTIAL
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF BELILOVE CO. ENGINEERS. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF BELILOVE CO. ENGINEERS IS PROHIBITED.

UNLESS OTHERWISE SPECIFIED:		BCE	
DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL ± ANGULAR: MACH ± BEND ± TWO PLACE DECIMAL ± THREE PLACE DECIMAL ±		TITLE: CERAWATT 800°C HEATER	
INTERPRET GEOMETRIC TOLERANCING PER:		SIZE	DWG. NO.
MATERIAL ALUMINA		A	BCE10010
FINISH SEE DWG			REV A
DO NOT SCALE DRAWING		SCALE: 1:2	WEIGHT: N/A
		SHEET 1 OF 1	